

Schleifriefen im Untergrund zeichnen sich als Riefen in der Reparaturalackoberfläche ab.

## URSACHEN

- 1| Der Untergrund wurde mit einem zu groben Schleifmittel bearbeitet. Der Lack schrumpft in den Riefen aufgrund der dort höheren Schichtdicke stärker.
- 2| Die vorgeschriebenen Trockenzeiten wurden bei den Grundmaterialien nicht eingehalten: Die Schleifriefen werden durch die Anquellung des Grundmaterials und Beifallen nach der Lacktrocknung deutlich sichtbar.
- 3| Zu dünne Schichten von Füller oder Decklack decken die Schleifriefen in tieferen Schichten nicht ab.
- 4| Falsche Schleiftechnik und/oder -geräte.

## VERMEIDUNG

- 1| Empfohlene Schleifpapierkörnungen einsetzen (Spachtelbereich P80/150, Grundfüller-/Füllerbereich P 240 – siehe technische Information). – Schleifkontrollfarbe verwenden.
- 2| Vorgeschriebene Trocknung einhalten.
- 3| Vorgeschriebene Schichtdicken einhalten.
- 4| Schleifmaschine in ruhigem Zustand aufsetzen, dann erst einschalten. Beim Füllertrockenschliff darf der Hub des Exzenters max. 5 mm betragen.

## REPARATUR

Anschleifen und Neuaufbau mit geeigneten Grund- und/oder Decklackmaterialien.

## DISCLAIMER

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our products, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the products for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights etc. given herein are for general information purpose only; they may change without prior information and do not constitute the agreed contractual quality of the products (product specification). The latest version supersedes all previous versions. You can obtain the latest version from our website at [www.rmpaint.com](http://www.rmpaint.com) or directly from your sales partner. It is the responsibility of the recipient of our products to ensure that any proprietary rights and existing laws and legislation are observed.