

ONYX ACTIVATOR

A 2210

Waterborne basecoat activator

Application:

- For special applications recommended by car manufacturers or for use under C 2A40 clear coat, the usage of ONYX ACTIVATOR would be necessary in ONYX HD basecoat.
- Additive for ONYX HD and for use in solid-color basecoats applied as a ground coat in ONYX HD 3-layer systems to improve tape resistance and hardness.
- If clear coat will be applied after the base coat application, please ensure this is done within 4 hours.

Solid Content	78 %
Density	1.03-1.13 g/cm ³
Storage temperature	5-45 °C
Shelf life	24 months

Please note: For automotive refinish, repair instructions of vehicle manufacturers, in particular regarding installed sensor technology, must always be observed in addition to the processing instructions given within this document.

Safety advice:

It cannot be ruled out that this product contains particles < 0.1 µm.

The products are suitable for professional use only.

For the use of this product please adhere to the actual safety recommendations and the personal protective equipment.

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our products, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the products for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights etc. given herein are for general information purpose only; they may change without prior information and do not constitute the agreed contractual quality of the products (product specification). The latest version supersedes all previous versions. You can obtain the latest version from our website at www.rmpaint.com or directly from your sales partner. It is the responsibility of the recipient of our products to ensure that any proprietary rights and existing laws and legislation are observed.

